



Commissioning Lighting Control Systems: 3 sides of the coin

Pete Samaras, PE, LC, LEED AP, DPR Construction
Lyn Gomes, kW Engineering

AIA Quality Assurance



The Building Commissioning Association is a Registered Provider with The American Institute of Architects Continuing Education Systems (AIA/CES). Credit(s) earned on completion of this program will be reported to AIA/CES for AIA members. Certificates of the Completion for both AIA members and non-AIA members are available upon request.

This program is registered with AIA/CES for continuing professional education. As such, it does not include content that may be deemed or construed to be an approval or endorsement by the AIA of any material of construction or any method or manner of handling, using, distributing, or dealing in any material or product.


Questions related to specific materials, methods, and services will be addressed at the conclusion of this presentation.

Learning Objectives

- At the end of this session you will be able to:
 1. Make intelligent comments in the design review that would improve the energy efficiency and the quality of bids
 2. Review a lighting controls sequence of operation with confidence
 3. Recognize when lighting control sequences require manufacturer-specific sequences instead of generic sequences that can be used across many projects and know where to go to find that information in manufacturer literature
 4. Identify maintainability issues for lighting controls in design review, just like mechanical equipment

What We'll Cover

- Perspective
- Lighting Control Basics
 - Components
 - Systems
- Design
 - Reviews
 - Sequences of operation
 - Productive comments
- Maintainability
- Constructability challenges
- Trends



Perspective: How we got here

- On/Off to DDC Time Warp
 - HVAC - 40 years
 - Lighting – 5 years
- Hot Potato
 - Lighting designers
 - Electrical engineers
 - Contractor
 - CxP

	HVAC	LIGHTING/ ELECTRICAL
Consultants	One: HVAC & Controls	Two: Lighting Circuiting
Deliverable	SOO	No standard
Design driver	Client's ability to maintain	Consultant's standard/ opinion
Implementation	HVAC Controls Sub-contractor	Electrical Sub

Perspective: IRL

HOT POTATOES....

- Or just pass it onto the Cx why don't we...



3.5 ACCEPTANCE TESTING SUPPORT SERVICES

- A. On all California projects, a certified lighting controls acceptance test technician (CLCATT) must verify the installation of the lighting control system. Manufacturer should include an extra day of factory technician's time to assist the CLCATT review the functionality and settings of the lighting control hardware per the requirements in the California State forms. It will be the CLCATT's responsibility to create and complete any forms required for the commissioning process, although the manufacturer or contractor may offer spreadsheets and/or printouts to assist the CLCATT with this task.

END OF SECTION

Perspective: IRL

HOT POTATOES....

- What are the problems with this Sequence of Operation?

Sequence: Dimmed lights are controlled in this space as (5) scenes.

ON: The normal power lights turn via switch station.


ADJUST: The scenes are adjusted using raise/lower control and lights are adjusted by selecting a scene button. The lights will continuously adjust to maintain a preset footcandle level based on the scene at +30" based on the available daylight within the space. The preset control module is located in the AV room for programming. An override switch with shade control shall be located at the door. Local over-ride switches shall provide 120 minutes of additional illumination.

OFF: After the space has been vacant for 15 minutes, the lights will automatically turn off.

ADDITIONAL CONTROL: Coordinate shade control with scene presets.

Perspective: The CxP's role

- Cx brings them all together
- Guide (aka “Cat Herder”)
 - Your input is critical
 - Understand big picture
- You must know:
 - Where we came from
 - What you’re talking about



The Designer(s)

What is their thought process?



- Lighting Consultant:
 - Often Partial scope (Front of House/Public spaces only)
 - Design Services to 100%DD or 50%CD level
 - Not fully engaged for Construction/Bid Set
- Architect:
 - Creates base plans
 - Often selects decorative lights/scones (if not included in lighting designer's package)
 - Makes changes
- Electrical Engineer:
 - Often responsible for BoH areas
 - Has to pull together the latest base plans/designs from the Architect/Lighting Consultant
 - Responsible for Circuiting
 - Documents the controls in the Permit/Bid Set

The Designer(s)

What's Missing???



- Lighting Consultant:
 - Not responsible for complete system
 - Not involved during construction when design is refined
 - Not responsible for circuiting (thus controls/details)
- Architect:
 - Makes changes to base plans (forgets to share with team)
 - Doesn't address control intent
 - Did I mention? ...Makes changes*
- Electrical Engineer:
 - Is often not involved in the OAC meetings where users discuss operational needs.
 - Often defaults to the Manufacturer's recommendations
 - Often defaults to the code requirements (code minimum)
 - Struggles with documentation with multiple named specs




Basic Components

- Occupancy sensors
- Daylighting
- Timeclocks, Janitor Overrides, Scene Controllers

Occupancy Sensors


- Types:
 - PIR (Passive InfraRed)
 - Ultrasonic
 - Microphonic
 - Dual Technology
- Trigger/Retrigger Occupancy/Vacancy
- Delay to Off (Dwell)
- Coverage range
- Location



Occupancy Sensor Technologies





Photocells/Daylight Sensors



- Types
 - Open loop
 - Closed loop
 - Combo
 - skylight
 - Technology
 - Affects placement
- Coverage range
- Closed vs open loop
- Mounting location
- Not too high
 - Not obstructed
 - No hot spots


Timeclocks, Janitor Overrides, Scene Control

- Shown on drawings?
- Timeclock
 - Hours of operation
 - Sweeps
 - Zones
- Janitor Override
 - Dwell
 - Retrigger?
- Scene Control
 - Labels
 - Zones
 - Sequence



Lighting Control Systems

What are we dealing with?



Lighting Control Systems


What are we dealing with?

- **Standalone**
 - Doesn't talk to anyone but itself
 - Usually single function
 - Local programming
- **Local Integration**
 - Multiple devices / inputs
 - Local programming
 - Local control
 - Additional inputs
- **Networked / Intelligent**
 - Wired or Wireless
 - Addressable
 - Intelligent Fixtures

Lighting Control Systems

Standalone

Sample Connection Diagram with Dimming Switches and Plug Load Control




Lighting Control Systems

- **Standalone**
 - Doesn't talk to anyone but itself
 - Usually single function
 - Local programming
- **Local Integration**
 - Multiple devices / inputs
 - Local programming
 - Local control
 - Additional inputs
- **Networked / Intelligent**
 - Wired or Wireless
 - Addressable
 - Intelligent Fixtures

Lighting Control Systems

Local Integration



Each segment network can connect up to 40 local networks for centralized monitoring and control



Lighting Control Systems

- **Standalone**
 - Doesn't talk to anyone but itself
 - Usually single function
 - Local programming
- **Local Integration**
 - Multiple devices / inputs
 - Local programming
 - Local control
 - Additional inputs
- **Networked / Intelligent**
 - Wired or Wireless
 - Addressable
 - Intelligent Fixtures

Networked Lighting Control Systems

Capabilities

- Layer multiple control strategies
- Customize / reconfigure
- Integrate with HVAC, security, etc.
- Monitoring
 - Performance
 - Energy use




Fully Networked

- Remote programming
- I/O
 - Local controls
 - Remote inputs/controls
 - To/From Multiple devices
- Wired
 - Network
- Wireless
 - Network bridge


Networked / Intelligent Lighting Control Diagram

Addressable



Networked / Intelligent Lighting Control Diagram

Wired -OR- Wireless



Beyond the Perspective and Basics

Implementation

© 2000 Randy Glasbergen.
www.glasbergen.com



"THE COMPUTER SAYS I NEED TO UPGRADE MY BRAIN
TO BE COMPATIBLE WITH ITS NEW SOFTWARE."

Owner's Project Requirements (OPR)

- Owner and User Requirements
 - Energy savings goals
 - Material quality
 - Future expansion
- IEQ
 - Occupancy schedules
 - Target footcandles and temperatures
 - Occupancy sensor type and time to off
 - Switching: Checkerboarding vs dimming
- Level of automation
- O&M
 - Maintenance expectations
 - Preferred manufacturer
- Target energy savings – up to 70%
 - Occupancy control 35-40%
 - Daylighting 10-30%
 - Manual Dimming 10%
 - Direct/indirect fixtures 10-40%
 - Demand Response 10% overall, 20%+ during event



Basis of Design (BOD)

- Design assumptions
- Basic control strategies
 - Timeclocks, janitor overrides
 - Occupancy control
 - Integrate with HVAC?
 - Daylighting
 - Demand response
 - Outdoor lighting
 - Manual dimming
 - Which spaces?
 - Task tuning
- Manufacturer
- Standalone or Networked?



Design Review

- Encourage sole-source
 - Parallels with HVAC Controls
- Encourage SOOs
 - Lay it out for them
 - Invest in a go-to explanation
 - Can the product do what the SOO asks?
 - Examples
 - daylighting control + continuous dimming and non-dimming ballasts
 - ADR with standalone system
 - Bathrooms set on vacancy mode

Reviewing the Lighting Controls

Don't Be Caught in a Dark Bathroom with Your Pants Down

- Lighting controls legend
 - Symbols should differ for model type
 - Hallway occ sensor vs office occ sensor
- Occ Sensor application
 - Ultrasonic or Dual Technology Sensors in spaces with barriers
 - Coverage pattern matches application & area
- Fixture schedule
 - Lamp type
 - Ballast/driver type
- Specs
 - Sensors
 - Control system
 - Standalone or Networked?



More Simple Design Checks

- Daylighting
 - Fixtures can do dimming
 - Number of photocells match control type
- Demand Response
 - Disaggregated zones
 - Dimming
- Timeclock
 - Hours of operation
 - Zones controlled
- Overrides
 - Locations
 - Zones
 - Time delay



Creating and Reviewing Sequences of Operation (SoO)

***DO YOU WANT TO
BUILD A ...***

...A SYSTEM?

...A PLATFORM?



General Process

Inputs	General Design Intent or Strategy during normal Operation	Modifications: 1	Modifications: 2	Modifications: 3
Photo-sensor / Daylighting				
Occupancy Sensing				
Tuning				
Personal Controls				

General Process


Inputs	General Design Intent or Strategy during normal Operation	Modifications: 1	Modifications: 2	Modifications: 3
Photo-sensor / Daylighting	Automatically balance available daylight using dimmable electric lighting to provide 50FC at +30" at all occupied times			
Occupancy Sensing	Reduce Light levels in corridors, stairwells, & unoccupied spaces during time of vacancy			
Tuning	Reduce light levels on area basis to correct for over-lighting			
Personal Controls	Light levels are selected based on local user preference			

General Process

Inputs	General Design Intent or Strategy during normal Operation	Modifications: 1 After hours / Weekends	Modifications: 2 ADR	Modifications: 3 ADR – Alt.
Photo-sensor / Daylighting	Automatically balance available daylight using dimmable electric lighting to provide 50FC at +30" at all occupied times	No Mod.	Reduce set point to 20FC	
Occupancy Sensing	Reduce Light levels in corridors, stairwells, & unoccupied spaces during time of vacancy	Turn light off in corridors, stairwells and unoccupied spaces when vacant	Turn light off in corridors, stairwells and unoccupied spaces when vacant	Reduce timeout intervals
Tuning	Reduce light levels on area basis to correct for over-lighting	No Mod.	Reduce light levels even further	
Personal Controls	Light levels are selected based on local user preference	No Mod.	Light levels prevented from exceeding set level	

Sequence of Operations Structure

- Components
 - OS, PC, BMS, Time of Day
- Their role
 - Fixture-integrated
 - Standalone
- Information flow:
 - Input
 - Associated Output
- Communication protocol
 - Wired
 - Wireless
 - BACNet, ZigBee, other...



SoO's come in numerous forms

- | | |
|-----------------------------------|-----------|
| • Narrative/Descriptive: | Pros/Cons |
| • Tables or Operational forms: | Pros/Cons |
| • Graphic: | Pros/Cons |
| • Details with Notes (Pictorial): | Pros/Cons |
| • Manufacturer Checklist: | Pros/Cons |

Example SoO: Narrative/Descriptive

3.5 LIGHTING CONTROL SEQUENCE OF OPERATION

- A. The network control system shall utilize Lumen Maintenance strategies to reduce energy waste in initial installation. All luminaires shall be dimmed to a maximum output of 80% with the capability to increase output over the course of the lighting systems rated life for consistent illuminance levels. Fine-tuning of acceptable illuminance levels for task tuning shall be done after furniture and finishes are completely installed.
- B. Luminaires over workstations in the open office shall include compact sensors integrated in the housing. When occupancy is undetected, open office luminaires shall dim to 30% output during business hours to avoid dark sections of the open office. Those luminaires shall turn-off during non-business hours when occupancy is undetected.
 - 1. Compact sensors shall be installed in 4' or 8' each section of continuous rows of luminaires as specified in the luminaire schedule.
 - a. Occupancy settings shall include all sections and rows of luminaires within a cluster of workstations.
 - b. Photosensors settings shall include sections of luminaires within primary and secondary daylight zones.
- C. All luminaire types other than the open office shall turn-off during non-occupancy at all times.
- D. Business hours and holiday scheduling will be determined by the End User.
- E. All sensors shall incorporate a photosensor set to maintain 30 footcandles on the work surface where contributing daylight is present.
- F. Task tuning for spaces where specific illuminance is preferred, personal control, and multi-scene settings will be determined by the End User with the assistance of the Lighting Designer.

Example SoO: Tables / Operational Form

CALIFORNIA TITLE 24 SEQUENCE OF OPERATIONS For New Construction and TI Interior Spaces			Time Schedules									
			DAY	MON	TUES	WED	THURS	FRI	Attached Schedule if needed	SAT	SUN	
AO: Auto ON			Weekdays									
MO: Manual ON			Operating Hours									
MO/AO: Manual ON and Auto OFF			After Operating Hours									
PO/MO: Partial Auto On, Manual to achieve FULL ON. When Unoccupied lighting power is reduced by 50%.			Weekend									
POS/AO: Partial ON/OFF. Lighting is turned on by time clock to 50% (or by OS first ON during operating hours triggered by occupant). When Occupied lights automatically go to full output. When Unoccupied lighting power reduced by 50% automatically.			Operating Hours									
PO2-5/AO: Parking Garage Only. Partial ON/OFF. Lighting is turned on by time clock to 50% (or by OS first ON during operating hours triggered by occupant). When Occupied lights automatically go to full output. When Unoccupied lighting power reduced by 20-50% automatically.			After Operating Hours									
MG: Motion Group												

Sequence of Operation is meant as a general guideline only. Although most requirements are shown below, individual projects should review T24 and adjust to projects as required.








Update January 26, 2016 v8.3


MANDATORY	BEST PRACTICE	EXEMPT
PROFILES (adjusted as needed for site conditions)	Task Tuning lowers MAXIMUM light output to Target Foot Candle Level for Energy Savings	130.1(a) AREA CONTROLS (x) Wall Switch - Wall Control - Keypad On/Raise Off/Lower (Scene Control Optional) General lighting must be controlled separately display, ornamental, track lighting, accent lighting, etc. all controlled separately
By Space Type - Most common space types are defined below	Maximum Light Output (Task Tuning) TARGET DESIGN or reduced to 80% output (depending on furniture and finishes typically can dim to 60% light output)	130.1(b) MULTI LEVEL 130.1(c) SENSOR BEHAVIOR 130.1(c) AUTOMATIC SHUTOFF Occupancy Sensor During Operating Hours 130.1(c) AUTOMATIC SHUT OFF Occupancy Sensor During Non-Operating Hours (Auto Shutoff Required) 130.1(c) AUTO SHUT OFF Time Schedules 130.1(d) AUTOMATIC DAYLIGHT CONTROLS (primary) exempt if < 120w or < 100 sq ft or less than 24sq ft glazing 130.1(d) AUTOMATIC DAYLIGHT CONTROL (secondary) exempt if < 120w or < 100 sq ft or less than 24sq ft glazing 130.1(d) AUTOMATIC DAYLIGHT CONTROL (skylight) exempt if < 120w or < 100 sq ft 130.1(e) Mandatory AUTO-DEMAND RESPONSE shall reduce light level by 15% if space or building is > 10k sq ft. Optional Demand Response 130.5(d) PLUS LOAD SHUTOFF (receptacle) required in New or TI construction when 6' of standard receptacle

INTERIOR LIGHTING & RECEPTACLE CONTROLS SEQUENCE OF OPERATION		
ROOM TYPE	FUNCTION	REMARKS
1 Atrium	OCCUPANCY SENSOR - MANUAL ON OCCUPANCY SENSOR - AUTO ON OCCUPANCY SENSOR - AUTO OFF CONTINUOUS DIMMING TO OFF ON/OFF SWITCH MULTI ZONE DIMMING AUTO TIME CLOCK ON AUTO TIME CLOCK OFF DAY LIGHT SENSING OVERRIDE SWITCH CONTROL SET LIGHT LEVEL TO 100% ON ACCEPTANCE TESTING OF CONTROLS BY CLCAIT	
2 Breakroom/Kitchenette		
3 Cafeteria Serving Area		
4 Cafeteria Prep		
5 Classrooms		
PRIVATE OFFICE < 250 FT ²		
BREAK ROOMS		
STAIRS		
SMALL RESTROOMS < 100 FT ²		DIM TO 50% WHEN UNOCCUPIED/'ON' AND 'OFF' TIME SET PER OWNER.
ELECTRICAL/MECHANICAL/UTILITY ROOMS		
RETAIL/SORTING		'ON' AND 'OFF' TIME SET PER OWNER.
CONTROLLED RECEPTACLES		

GENERAL NOTE:
LIGHTING CONTROL SYSTEMS SHALL BE CAPABLE OF MEETING DEMAND RESPONSE REQUIREMENTS OF CALIFORNIA TITLE 24.

Example SoO: Graphic

ZONE CONTROL KEY		
SPACE TYPE	EQUIPMENT	SEQUENCE
 LEVEL 2 - ZONE 1 BUILDING CORE	SWITCH	ON: LIGHTS WILL AUTOMATICALLY TURN ON AT BEGINNING OF WORKDAY. OFF: AT END OF WORKDAY LIGHTS WILL BE SHUT OFF. IF OVERRIDE SWITCH IS SELECTED A 120 MINUTE DELAY WILL BEGIN.
 LEVEL 2 - ZONE 2 OPEN OFFICE SOUTHEAST	SWITCH	ON: LIGHTS WILL AUTOMATICALLY TURN ON AT BEGINNING OF WORKDAY. OFF: AT END OF WORKDAY LIGHTS WILL BE SHUT OFF. IF OVERRIDE SWITCH IS SELECTED A 120 MINUTE DELAY WILL BEGIN.
 LEVEL 2 - ZONE 3 OPEN OFFICE SOUTHWEST	SWITCH	ON: LIGHTS WILL AUTOMATICALLY TURN ON AT BEGINNING OF WORKDAY. OFF: AT END OF WORKDAY LIGHTS WILL BE SHUT OFF. IF OVERRIDE SWITCH IS SELECTED A 120 MINUTE DELAY WILL BEGIN.
 LEVEL 2 - ZONE 4 OPEN OFFICE NORTHWEST	SWITCH	ON: LIGHTS WILL AUTOMATICALLY TURN ON AT BEGINNING OF WORKDAY. OFF: AT END OF WORKDAY LIGHTS WILL BE SHUT OFF. IF OVERRIDE SWITCH IS SELECTED A 120 MINUTE DELAY WILL BEGIN.
 LEVEL 2 - ZONE 5 OPEN OFFICE NORTHEAST	SWITCH	ON: LIGHTS WILL AUTOMATICALLY TURN ON AT BEGINNING OF WORKDAY. OFF: AT END OF WORKDAY LIGHTS WILL BE SHUT OFF. IF OVERRIDE SWITCH IS SELECTED A 120 MINUTE DELAY WILL BEGIN.
 LEVEL 2 - TRAINING ROOM PERIMETER ZONE AS SHOWN ON LIGHTING PLAN	DIMMING	ON: LIGHTS MANUALLY TURN ON USING LOCAL SCENE CONTROL. ADJUST: LIGHTING IS ADJUSTED BETWEEN PRESET SCENE ADJUST TO MAINTAIN 50 FOOT CANDLES AT THIRTY INCHES. OFF: LIGHTS AUTOMATICALLY TURN OFF WHEN NO MOTION DETECTED FOR 15 MINUTES.
 LEVEL 2 - TRAINING ROOM INTERIOR ZONE AS SHOWN ON LIGHTING PLAN	DIMMING	ON: LIGHTS MANUALLY TURN ON USING LOCAL SCENE CONTROL. ADJUST: LIGHTING IS ADJUSTED BETWEEN PRESET SCENE ADJUST TO MAINTAIN 50 FOOT CANDLES AT THIRTY INCHES. OFF: LIGHTS AUTOMATICALLY TURN OFF WHEN NO MOTION DETECTED FOR 15 MINUTES.



Example SoO: Details / Pictorial


TITLE 24 SYMBOL LEGEND

GN = GENERAL LIGHTING FIXTURE

FD = FLOOR DISPLAY FIXTURE

WD = WALL DISPLAY FIXTURE

OR = ORNAMENTAL DISPLAY FIXTURE




LIGHTING CODED NOTES

- (101) OCCUPANCY SENSOR SWITCH FOR CONTROL OF ROOM LIGHTING. OCCUPANCY SWITCH SHALL BE A WATT STOPPER PW100. SET SWITCH FOR MAXIMUM SENSITIVITY. CONTROL AND ADJUST SWITCH TO MAINTAIN LIGHTS ON FOR 15 MINUTES AFTER LAST MOTION IS DETECTED. SWITCH SHALL BE ADJUSTED TO OVERRIDE THE LIGHT LEVEL ENERGY SAVING FEATURE. DIP SWITCH SETTING OF THE SWITCHES BENEATH THE COVER SHALL BE SET AS FOLLOWS:

ON - DIP 2,3,6
OFF - DIP 1,4,5,7,8
NOT USED - DIP 9




- (102) BYPASS BUTTON LIGHTING CONTROL SWITCH. DIP SWITCH SETTINGS ARE FACTORY SET FOR 2 HOURS.



ELECTRICAL CONTRACTOR SHALL ROUTE THE SWITCHED HOT LEG FROM THE LOAD SIDE OF THE WATTSTOPPER DLM MODULES THROUGH THE CONTACTOR SO AS NOT TO SHUT OFF POWER COMPLETELY TO THE WATTSTOPPER DLM MODULES.

Example SoO: Pictorial / Narrative



Example SoO: Pictorial / Narrative

Sequence of Operations	
Custom Sequence for 206 Copy	
Areas Affected	2nd Floor\206 Copy
Lights Controlled	Type K
Light Controls	<i>Lights</i> : Dimmed lights are controlled in this area as described below.
	<i>Occupancy</i> : Lights automatically turn on to the lessor of 80% or Daylight Level when the user enters the area and <u>15</u> minutes after the room has been vacated, the lights will automatically turn off. Type H3 Lights will accept occupancy signals from OS within the area and remain on for <u>30</u> minutes after the room has been vacated.
	<i>Daylighting</i> : Lights will automatically adjust to harvest daylighting. Target FC level in this area is <u>25FC</u> . When maximum daylighting is achieved, the lights will dim to low end and turn off when overall light level is <u>40FC</u> (measured on the desktop) - Lights to accept signal from PC mounted within each corresponding control zone area.
	<i>Time of Day Schedule</i> : Currently no time of day scheduling is anticipated for this area. Time of day scheduling may be added at a later date should it become necessary to keep the lights on during normal business hours.
	<i>Upper Level Trim</i> : Sewt upper level trip at 80% output.
	<i>Manual Wall Control</i> : Pico dimmer switch mounted on wall. One dedicated Pico dimmer per control zone as defined below. To control lights manually, the user can select On+Off with Raise/Lower using the control station.
Additional Controls	Emergency Lights: Egress lighting in this area will be provided by separate, self contained emergency lighting units.
	<i>Kill Switch</i> : All lights on Quantum System, except Lighting at Fitness, Stair 1, and Stair 2; and D6 at entry to turn off upon signal from BMS / Kill Switch Signal that the office is now empty and secure. Type D6 lights will turn off 15 minutes after the space has been vacated. Stairs 1 and 2 remain occupancy based control via their respective occupancy sensors.
	<i>Demand Response</i> : Upon signal from BMS, reduce overall lighting energy by and additional 30%. For example if the lights are at 80%, reduce them further to 56% output.
Quantum	This area will be part of Quantum System. Other requirements for this system include BACnet for Building Management System Integration. Report Occupancy status, and lighting status to BMS. Accept inputs from BMS for Demand Response, additional dimming, and Kill Switch.
Other	PICO: Master Raise/Lower of Type K lights in this room.

Example SoO: Mfr's Check Lists...

ELECTRICAL CONTRACTOR'S PRE-COMMISSIONING CHECKS - GENERAL REQUIREMENTS		
1	Lighting Control System Turnover to Lutron for Commissioning Prerequisites	Before turning a Lighting Control System (LCS) over to Lutron for commissioning, the Electrical Contractor (EC) must confirm that:
		a) All panels, wall controls, and other items of LCS equipment are fully installed and wired in accordance with applicable installation instructions.
		b) All wiring terminations were subject to a "Wire Pull" test at the termination point. Specifically, using appropriate electrical safety precautions, gently tug on each wire termination and ensure that the wire is secure.
		c) All LCS controlled lighting fixtures are permanently installed, wired, and tested to confirm that they operate at full brightness.
		d) The system specific Electrical Contractor Pre-Commissioning checks (e.g. EcoSystem, Panel Based Systems, Grafik QS, etc.) have been completed satisfactorily.
		e) The Bypass Jumpers are still in place in the XP (switching or relay) and LP (dimming) panels.
		f) All spaces are "move-in ready" (furniture, carpeting, shades, blinds, wall covering, pictures, etc. are installed) prior to daylight sensor calibration and daylight harvesting commissioning.
		g) Lutron personnel will have unrestricted and unobstructed access to the LCS equipment being commissioned.
		h) Lutron personnel will be able to turn the LCS controlled lighting fixtures "on" and "off" without restriction.
		i) Lutron personnel will be free to operate the lighting circuit breakers in the Lutron Lighting Distribution Panels without restriction.
		j) The final, approved Load Schedule and Control Specifications have been supplied to Lutron.
2	Commissioning Objectives	k) The Pre-Commissioning Startup Checklist(s) has been completed satisfactorily and faxed to Lutron.
		The goals of the Commissioning process are (as dictated by the installed equipment):
		a) Verify LCS components are installed in the approved, documented locations using proper mounting techniques
		b) Verify proper feed and load wiring at the Lighting Distribution, Dimming, and Switching Panels
		c) Verify communications wiring
		d) Check panels for correct load types and ensure circuit loading is within published limits
		e) Energize the Lutron Hubs/Processor and upload the databases
		f) Address ballasts, QS devices, Panels
		g) Remove bypass jumpers
		h) Set up, and then verify, the proper operation of every circuit and control device in the system

Example SoO: Mfr's Check Lists...

ELECTRICAL CONTRACTOR'S PRE-COMMISSIONING CHECKS - GENERAL REQUIREMENTS		
		<ul style="list-style-type: none"> i) Verify the operation of Lutron's integration equipment (does not include commissioning of other manufacturer's equipment with which Lutron is integrating) j) Assist Electrical Contractor in troubleshooting installation issues and miss-wires k) Obtain sign-off on system function, excluding the Graphical User Interface (GUI) l) Identify the Owner's GUI design contact (if purchased on the BOM)
3	Documentation and Assistance Required for Startup Visit	<p>To help ensure that the Lutron Field Service Engineer(s) have sufficient time to complete the Startup activities, Lutron requests that the EC have the following items available upon their arrival on site (as applicable):</p> <ul style="list-style-type: none"> a) A complete set of the "Final" LCS drawings and Specifications b) A complete list of system modifications and field changes c) Accurate Load Schedules posted on the door of each Lighting Panel or in a folder if all panels are clearly and permanently labeled d) "Sequence of Operation" specifications and settings approved by an authorized party (if not documented in the submittal) e) "Timeclock Events" specifications and settings approved by an authorized party f) Door keys, badges and/or security codes, required for access into secured areas g) Electrician assistance
4	Caution	<p>Please note that extra charges (overtime/return visit) may result if additional on-site time is required due to:</p> <ul style="list-style-type: none"> a) Incomplete system preparation b) Improper equipment installation c) Excessive installation errors d) Unexpected system design modifications e) Excessive system design modifications f) The unexpected presence of non-Lutron supplied interface equipment g) The need to revise "Sequence of Operation" settings due to incorrect information being provided

Manufacturer-Specific Requirements

The case for sole-source

- Manufacturers adjustment parameters are different
 - This affects the sequence
- Daylighting sexample:
 - Lutron - gain
 - Wattstopper - ramp rate, FC level
- Occupancy sensor example:
 - Wattstopper - US/PIR trigger/retrigger
 - Nlight - microphonics, sensor & room controller delays
- Prepare:
 - Review literature
 - Knowledgeable Rep
 - Training

Do your homework

- Control system manufacturer (in BOD)
- Research product during SD
- Meet with Mfr/Rep to understand programming constraints.
- Identify compromises (often necessary)
- SoO is a living document
 - Updates throughout design
 - During submittal process
- Include lighting in controls integration meeting
- Bottom Line:
 - You need to be smarter than the Designers and the Contractors.


Anatomy of a productive comment

Prevent drama

- State what the design says/shows
 - Include pictures
- Explain why its needed
 - Standards? OPR? Agreement with BOD? Best practice?
- Put it in context
 - Explain the consequences of not implementing it
 - Lay out your case
- Make your recommendation
 - Be diplomatic
- Bonus points:
 - Priority
 - Making it easy
 - An example
 - Reference/further reading

Implementable comments

- What do we see?
- What's wrong?
- Significance?
- How to Fix it?
- What do we recommend?



Recommendations that aren't controversial

- Be respectful
 - It's not about you – it's about the project
- Establish a positive tone
- Avoid Authoritarian tone
 - Best: “*We recommend...*”
 - Bad: “*In our opinion...*”
- Provide an example – make it easy for them

I demand respect and I'm gonna talk down to everyone until I get it!



Example Design Statement

Description What we see	Dwg	Recommended Changes
The mechanical drawings indicate that occupancy sensors will be used in the mechanical control sequences.	M6.3 E5.1	Coordinate with the mechanical engineer and make it clear that the lighting control system will need to support the HVAC control system.
It is not clear on the electrical drawings that the WattStopper system will support the exchange of this information to the HVAC controls.	What's wrong	<p>According to WattStopper, you can either:</p> <ol style="list-style-type: none"> 1. Add an LMRL-100 to each room, which has a contact closure that can relay occupancy status to the HVAC control system.
Bringing this point from the lighting control system to the BMS will be a significant effort (i.e. time and money for the contractor) and would require a fair amount of coordination with the lighting control vendor (more time & money). If the contractor misses it and then has to do the work they didn't budget for (but is contractually obligated to), there is a chance that the quality of workmanship will be deficient and the system may not work reliably.		<p>Significance</p> <p>If a Segment Manager is used on the project, it's possible to export a table of room status to the HVAC control system over BACnet/IP, but the two control systems must be on the same network.</p> <p>Clarify which option will be used and make it clear in the mechanical and electrical drawings which will be used.</p>
		Recommendation

Maintainability (don't buy cheap stuff)

- How is cheap achieved?
 - Product support
 - Quality
 - Set up/configuration
 - Installation
- Infant mortality
- Quality
 - Literature
 - Website
 - Phone support
- Cost
 - Installed cost vs first cost
 - Persistence of energy savings



Challenges faced by contractors

- GUESSWORK
- Impossible sequences
- “Performance specification”
- New technologies
- New codes



Trends.... Smart Lighting

- Embedded wireless
- Open Standard vs. “Spec-Lock”; Web Based
- New Value chains
- Data mining, IoT
- Luminaire Level Lighting Controls (LLLC)
- New protocols
 - Zig-Bee, Blue Tooth, DALI
- Addressable system
 - Point to point checking
- Auto-_____
 - Provisioning, Set-up, Formation, Cx
 - “Auto-_____” is only start-up!





Pete Samaras, PE, LC, LEED AP
Precon Manager, Lighting Designer

DPR Construction
petes@dpr.com
www.dpr.com



Lyn Gomes, PE, CCP, LEED AP, CLCATT
Senior Commissioning Provider

kW Engineering
lgomes@kw-engineering.com
www.kw-engineering.com

